

# NPP-4840-3R-100PECD

## 48x40 (Standard) Plastic Industrial Pallet



### Technical Data

Dimensions 48x40x5.6 inches (1219x1016x142 mm)  
Weight 20.0 lbs

#### Load Capacities

Static 6600 lbs  
Dynamic 2800 lbs  
Racking --

Entry 4-way  
Truckload Qty 540  
Stack TL 18

TL (truckload) quantities are approximate and may vary by transport equipment or other factors.

### Handling Data

<b>Nestable</b> No	<b>Reusability</b> One-Way	<b>ISPM-15 Exempt</b> Yes
<b>Stackable</b> Yes	<b>Destination</b> Export	<b>Food Grade</b> Yes, non-FDA
<b>Rackable</b> No	<b>Airfreight</b> No	<b>Pharmaceutical</b> Yes

### Materials and Colors

**Condition**  
New

<b>Material</b> HDPE/PP (Recycled) HDPE/PP (Virgin*)	<b>Color</b> Black Gray/Custom*
--	---------------------------------------

(High-Density Polyethylene/Polypropylene)

\*Custom colors and markings available in virgin material.  
(Minimum quantities required.)

### Deck Specs

**Top Deck**  
Closed

**Bottom Deck**  
3 Runner - Unidirectional Long Side

#### Available Options:

No skids (open) = CPP100  
No skids (closed) = NPP-4840-N-100#CD  
3 Runner snap-on skids\* (open) = CPP103  
3 Runner snap-on skids\* (open) = NPP-4840-3R-100#CD  
\*Order with skids off for lower shipping

### Features

- Intermittent anti-slip tabs on top deck
- Allows for safe double stacking
- Easy-to-clean hygienic design
- Suitable for packaged food items  
(not approved for direct food contact)
- Impervious to acids, fats, solvents and odors
- Resists water absorption & bacteria growth
- Inert to infestation, mold and mildew
- Consistently dimensionally accurate
- Exempt from ISPM 15 shipping regulations



## Nelson™

The Nelson Company

(443) 649-5294

[plastic@NelsonCompany.com](mailto:plastic@NelsonCompany.com)

[www.NelsonCompany.com](http://www.NelsonCompany.com)

[www.NelsonTechCenter.com](http://www.NelsonTechCenter.com)

Spec Sheet Generated On: 5/19/2024

Specs subject to change without notice. Provided for informational purposes only. Technical data are guideline values and may vary based on intended use, features, raw materials and environment. Nothing shall be construed as warranties or guarantees, express or implied, regarding products or their use, application, performance or otherwise.