# CPP326/ACM

# 48x40 (Standard) **Plastic Industrial Pallet**

### **Technical Data**

Dimensions Weight

Truckload Qty

Stack TL / LTL

48x40x5.9 inches (1219x1016x150 mm) 32.0 lbs

Load Capacities	
Static	17600 lbs
Dynamic	5300 lbs
Racking	1300 lbs
0	
Entry	4-way

300 lbs way 540 18 / 16

TL (truckload) and LTL (less-than-truckload) quantities are approximate and may vary by transport equipment or other factors. \_\_\_\_\_

# Handling Data

Nestable No

Stackable Yes

Rackable Yes

Reusability One-Way Destination Export

Airfreight Yes

**ISPM-15** Exempt Yes

**Food Grade** Yes, non-FDA

**Pharmaceutical** Yes





## **Materials and Colors**

Condition New

Material ACM (Recycled)

Color Black

# **Deck Specs**

Top Deck Open

**Bottom Deck** 6 Runner - Perimeter+2 Cross (cruciform perimeter base)

Available Options: Open Top = CPP32# Closed Top = CPP32#-C

CPP320 - No skids (nestable) CPP323 - 3 Runner snap-on skids\* CPP326 - 6 Runner snap-on skids\* \*Order with skids off for lower shipping cost

#### **Features**

- Allows for safe double stacking
- Easy-to-clean hygienic design
- Suitable for packaged food items (not approved for direct food contact)
- Impervious to acids, fats, solvents and odors
- Resists water absorption & bacteria growth
- . Inert to infestation, mold and mildew
- Consistently dimensionally accurate
- Exempt from ISPM 15 shipping regulations





Spec Sheet Generated On: 5/20/2024

Specs subject to change without notice. Provided for informational purposes only. Technical data are guideline values and may vary based on intended use, features, raw materials and environment. Nothing shall be construed as warranties or guarantees, express or implied, regarding products or their use, application, performance or otherwise.