# PS4840FP-ProFM

### 48x40 (Standard) **Plastic Industrial Pallet**

#### **Technical Data**

**Dimensions** 48x40x5.12 inches

Weight 43.5 lbs

**Load Capacities** 

30000 lbs Static Dynamic 4000 lbs ST Req Racking

4-way Entry Truckload Qty 600 20 / 18 Stack TL / LTL

Unit load Sample Tests (ST) are recommended to confirm successful use with specific applications and equipment. TL (truckload) and LTL (less-than-truckload) quantities are approximate and may vary by transport equipment or other factors.

#### **Handling Data**

Nestable Reusability No Multi-Trip

Stackable Destination Captive

Rackable Airfreight

Yes

ISPM-15 Exempt

**Food Grade** FDA Approved

**Pharmaceutical** 

Yes





#### **Materials and Colors**

Condition New

Material Color

**HDPF** Blue, Black, Gray

(High-Density Polyethylene)

#### **Deck Specs**

Top Deck Open

**Bottom Deck** 

6 Runner - Perimeter+2 Cross (cruciform perimeter base)

#### **Features**

FM approved options available for meeting fire rating requirements.

- Built for safe transportation and storage of pharmaceutical products.
- Meets decaBDE-free fire retardant standards
- Thicker leg design for better impact protection
- · Larger tapered forklift pockets
- Allows for safe double stacking
- Sanitary choice for strict drug manufacturing requirements
- Impervious to acids, fats, solvents and odors
- Resists water absorption & bacteria growth
- Inert to infestation, mold and mildew
- Consistently dimensionally accurate
- Exempt from ISPM 15 shipping regulations




www.NelsonTechCenter.com


## PS4840FP-ProFM


48x40 (Standard)
Plastic Industrial Pallet



### **Technical Drawings**







| SI |  |  |  |
|----|--|--|--|
|    |  |  |  |
|    |  |  |  |

| DIM "A" | DIM "B" | DIM "C" | DIM "D" | DIM "E" | DIM "F" | DIM "G" | DIM "H" | DIM "J" | DIM "K" | DIM "L" |
|---------|---------|---------|---------|---------|---------|---------|---------|---------|---------|---------|
| 48.062  | 40.052  | 6.068   | 10.073  | 7.76    | 10.113  | 13.818  | 7.009   | .751    | 3.630   | 5.132   |

TOLERANCE (+/-) 0.005 BASE PLUS .0025 PER INCH

