


NPP-4840-FP-PSG5.1FM

48x40 (Standard) Plastic Industrial Pallet



Technical Data

Dimensions 48x40x5.13 inches
Weight 34 lbs

Load Capacities


Static 20000 lbs
Dynamic 4000 lbs
Racking ST Req

Entry 4-way
Truckload Qty 600
Stack TL / LTL 20 / 18


Unit load Sample Tests (ST) are recommended to confirm successful use with specific applications and equipment. TL (truckload) and LTL (less-than-truckload) quantities are approximate and may vary by transport equipment or other factors.

Handling Data

Nestable No	Reusability Multi-Trip	ISPM-15 Exempt Yes
Stackable Yes	Destination Captive	Food Grade FDA Approved
Rackable Yes	Airfreight No	Pharmaceutical Yes



Bottom View



Materials and Colors

Condition
New

Material HDPE
Color Blue

(High-Density Polyethylene)

Deck Specs

Top Deck
Open

Bottom Deck
6 Runner - Perimeter+2 Cross
(cruciform perimeter base)

Full perimeter bottom deck design allows racking.
Manufacturer load rating = 4,000 lbs in supported rack.

Features

- Built for safe transportation and storage of pharmaceutical products.
- Meets decaBDE-free fire retardant standards
- FM approved for meeting fire rating requirements.
- Allows for safe double stacking
- Sanitary choice for strict drug manufacturing requirements
- Impervious to acids, fats, solvents and odors
- Resists water absorption & bacteria growth
- Inert to infestation, mold and mildew
- Consistently dimensionally accurate
- Exempt from ISPM 15 shipping regulations

NelsonTM

The Nelson Company

(443) 649-5294

plastic@NelsonCompany.com

www.NelsonCompany.com

www.NelsonTechCenter.com