

CP-1280-3R-Ene7CD

48x32 (Euro)

Plastic Industrial Pallet



Technical Data

Dimensions 47.2x31.5x6.2 inches (1200x800x157 mm)
Weight 39.5 lbs

Load Capacities

Static 8800 lbs
Dynamic 4400 lbs
Racking 2200 lbs

Entry 4-way
Truckload Qty 608
Stack TL / LTL 16 / 15

TL (truckload) and LTL (less-than-truckload) quantities are approximate and may vary by transport equipment or other factors.

Handling Data

Nestable No	Reusability Multi-Trip	ISPM-15 Exempt Yes
Stackable Yes	Destination Captive & Export	Food Grade No
Rackable Yes	Airfreight Yes	Pharmaceutical Yes

Materials and Colors

Condition
New

Material HDPE/PP (Recycled) HDPE/PP (Virgin*)	Color Black Gray/Custom*
--	---------------------------------------

(High-Density Polyethylene/Polypropylene)

*Custom colors and markings available in virgin material.
(Minimum quantities required.)

Deck Specs

Top Deck
Closed

Bottom Deck
3 Runner - Unidirectional Long Side

SHIP FROM
Mfg Plant
506 SeaCont (40') / 23 per Inverted Stack
US Facility
874 TL (53') / 23 per Inverted Stack
608 TL (53') / 16 per Stack
LTL 15 per Stack or 23 per Inverted Stack

Features

Note: CP-1280-3R-Ene7CD was previously known as NPP-1280-3R-Ene7CD

Ideal for closed loops or distribution chains across industry sectors including Electronics, Food, Retail, Medical + Pharma (FDA blue, red, green)

- Excellent choice for a high-traffic systems pallet
- Closed deck eliminates debris getting caught in pallet
- Anti-slip grommets available
- Standard size used across EU
- Design is popular in rail freight applications
- Allows for safe double stacking
- Sanitary choice for many pharmaceutical applications
- Impervious to acids, fats, solvents and odors
- Resists water absorption & bacteria growth
- Inert to infestation, mold and mildew
- Consistently dimensionally accurate
- Exempt from ISPM 15 shipping regulations



Nelson™

The Nelson Company
(443) 649-5294

plastic@NelsonCompany.com
www.NelsonCompany.com
www.NelsonTechCenter.com