

CP-1210-FP-ENi7CD

48x40 (Standard) Plastic Industrial Pallet



Technical Data

Dimensions 47.2x39.4x6.3 inches (1200x1000x160 mm)
Weight 50.5 lbs

Load Capacities

Static 11000 lbs
Dynamic 5500 lbs
Racking 2750 lbs

Entry 4-way
Truckload Qty 510
Stack TL / LTL 17 / 15

TL (truckload) and LTL (less-than-truckload) quantities are approximate and may vary by transport equipment or other factors.

Handling Data

Nestable No	Reusability Multi-Trip	ISPM-15 Exempt Yes
Stackable Yes	Destination Captive	Food Grade Yes, non-FDA
Rackable Yes	Airfreight No	Pharmaceutical Yes

Materials and Colors

Condition
New

Material HDPP (Recycled) HDPP (Virgin*)	Color Black (custom colors available) Gray/Custom*
--	---

(Impact Resistant HDPP)

*Custom colors and markings available in virgin material.
(Minimum quantities required.)

Deck Specs

Top Deck
Closed

Bottom Deck
6 Runner - Perimeter+2 Cross
(cruciform perimeter base)

Special Order Options:
3 Runner
Closed Deck
RFID Transponders
Fire Retardant
Individual Markings
Anti-Slip Grommets
FDA Blue Virgin Material

Features

Note: CP-1210-FP-ENi7CD was previously known as NPP-1210-FP-ENi7CD
Ideal for closed loops or distribution chains across industry sectors including Electronics, Food, Retail, Medical and Pharmaceutical.

- Excellent choice for high-traffic systems
- High performance at low cost
- Closed deck design eliminates debris getting caught in pallet
- Allows for safe double stacking
- Easy-to-clean hygienic design
- Suitable for packaged food items
(not approved for direct food contact)
- Impervious to acids, fats, solvents and odors
- Resists water absorption & bacteria growth
- Inert to infestation, mold and mildew
- Consistently dimensionally accurate
- Exempt from ISPM 15 shipping regulations



Nelson™

The Nelson Company
(443) 649-5294

plastic@NelsonCompany.com
www.NelsonCompany.com
www.NelsonTechCenter.com