

PG-4840-FP-NPT6R

48 x 40 (Standard US)

Plastic Pallet



Technical Data

Dimensions 47.2x39.4x6.5 inches (1200x1000x165 mm)
Weight 29.0 lbs

Load Capacities

Static 6,614 lbs
Dynamic 3,087 lbs
Racking 1,102 lbs

Entry 4-Way
Truckload Qty 540
Stack TL / LTL 18 / 16

TL (truckload) and LTL (less-than-truckload) quantities are approximate and may vary by transport equipment or other factors.

Handling Data

Nestable No	Reusability One-Way & Multi-Trip	ISPM-15 Exempt Yes
Stackable Yes	Destination Captive & Export	Food Grade Yes, non-FDA
Rackable Yes	Airfreight No	Pharmaceutical Yes

Materials and Colors

Condition New

Material HDPE/PP (Recycled) HDPE/PP (Virgin*) (High-Density Polyethylene/Polypropylene)	Color Black Gray/Custom* (Minimum quantities required.)
---	---

*Custom colors and markings available in virgin material.
(Minimum quantities required.)

Deck Specs

Top Deck Open

Bottom Deck
6 Runner - Perimeter+2 Cross
(cruciform perimeter base)

Available Options:

Anti-Slip Inserts
Individual Markings
PG-4840-N-NPT - No skids (nestable)
Order with skids off for lower shipping cost

Features

- Temp 0 F to +172 F
- Allows for safe double stacking
- Easy-to-clean hygienic design
- Suitable for packaged food items (*not approved for direct food contact*)
- Impervious to acids, fats, solvents and odors
- Resists water absorption & bacteria growth
- Inert to infestation, mold and mildew
- Consistently dimensionally accurate
- Exempt from ISPM 15 shipping regulations



Nelson™
The Nelson Company
(443) 649-5294
plastic@NelsonCompany.com
www.NelsonCompany.com
www.NelsonTechCenter.com

Spec Sheet Generated On: 9/22/2026

Specs subject to change without notice. Provided for informational purposes only. Technical data are guideline values and may vary based on intended use, features, raw materials and environment. Nothing shall be construed as warranties or guarantees, express or implied, regarding products or their use, application, performance or otherwise.